

**DEPARTMENT OF TRANSPORTATION**

DIVISION OF ENGINEERING SERVICES

OFFICE ENGINEER

1727 30<sup>th</sup> Street MS-43

P.O. BOX 168041

SACRAMENTO, CA 95816-8041

FAX (916) 227-6214

www.dot.ca.gov/hq/esc/oe



*Serious Drought.  
Help save water!*

January 30, 2015

07-LA-105,710-Var  
07-2W0604  
Project ID 0713000085

Addendum No. 1

Dear Contractor:

This addendum is being issued to the contract for CONSTRUCTION ON STATE HIGHWAY IN LOS ANGELES COUNTY AT VARIOUS LOCATIONS.

Submit bids for this work with the understanding and full consideration of this addendum. The revisions declared in this addendum are an essential part of the contract.

Bids for this work will be opened on Wednesday, February 11, 2015.

This addendum is being issued to revise the project plans and the *Notice to Bidders and Special Provisions*.

Project plan sheet 47 is replaced and attached for substitution for the like-numbered sheet.

Project plan sheet 47A is added and attached for addition to the project plans.

In the Special Provisions, Section 15.40.2B, "Replace the first paragraph of section 15.40.2B with:" is replaced as follows:

"Replace the first paragraph of section 15-4.02B with:"

In the Special Provisions, Section 51-2.02G, "Waterproof Joint Seal System," is replaced as attached.

Addendum No. 1  
Page 2  
January 30, 2015

07-LA-105,710-Var  
07-2W0604  
Project ID 0713000085

To *Bid* book holders:

Inquiries or questions in regard to this addendum must be communicated as a bidder inquiry and must be made as noted in the *Notice to Bidders* section of the *Notice to Bidders and Special Provisions*.

Submit the *Bid* book as described in the *Electronic Bidding Guide* at the Bidders' Exchange website.

**[http://www.dot.ca.gov/hq/esc/oe/electronic\\_bidding/electronic\\_bidding.html](http://www.dot.ca.gov/hq/esc/oe/electronic_bidding/electronic_bidding.html)**

Inform subcontractors and suppliers as necessary.

This addendum, EBS addendum file and attachments are available for the Contractors' download on the Web site:

**[http://www.dot.ca.gov/hq/esc/oe/project\\_ads\\_addenda/07/07-2W0604](http://www.dot.ca.gov/hq/esc/oe/project_ads_addenda/07/07-2W0604)**

If you are not a *Bid* book holder, but request a book to bid on this project, you must comply with the requirements of this letter before submitting your bid.

Sincerely,

  
for CARRIE BOWEN  
District Director

Attachments

**Add to section 51-2.02:**

**51-2.02G Waterproof Joint Seal System**

**51-2.02G(1) General**

Section 51-2.02G includes specifications for installing a waterproof joint seal system at the joints at the abutments of the existing water flume. Waterproof joint seal system includes waterproof joint seal and clamping system.

**51-2.02G(1)(a) Definitions**

Not used

**51-2.02G(1)(b) Submittals**

Submit current manufacturer's product data sheet, installation procedure, and MSDS.

Submit installation plan provided by manufacturer.

Submit shop drawings for the waterproof joint seal system, including the clamping system.

Submit certificates of compliance for waterproof joint seal.

**51-2.02G(1)(c) Quality Control and Assurance**

Not used

**51-2.02G(2) Materials**

**51-2.02G(2)(a) General**

Not used

**51-2.02G(2)(b) Waterproof Joint Seal**

Waterproof joint seal must be a flexible, reinforced omega-shaped rubber seal designed to accommodate the movement of the joint and to withstand water pressure of at least 5 psi.

Waterproof joint seal must be one of the following or equal:

1. Omega Seal OS 240-40, manufactured by Trelleborg Ridderkerk, B.V., Verlengde Kerkweg 15, 2985 AZ, Ridderkerk, P.O. Box 4007, 2980 GA, Ridderkerk, The Netherlands, Telephone: +31(0)180495596 or +31613857281.
2. ES Series Expansion Joint Seal ES 240-40, manufactured by Ekspan Limited, Compass Works, 410 Brightside Lane, Sheffield, S9 2SP, United Kingdom, Telephone: +44 (0)114 2611126.

Use of an equivalent waterproof joint seal must be authorized.

**51-2.02G(2)(c) Clamping System**

Materials for clamping system must comply with 75-1.03

Fabricate parts for clamping system as shown in authorized shop drawings.

**51-2.02G(3) Construction**

Install waterproof joint seal and clamping system as shown on the installation plan provided by manufacturer.

Clean all dirt, debris, water and other foreign material from the existing joint before installation.

Joint seal must not have joints or be field spliced.

Dispose of debris.

**51-2.02G(4) Payment**

Not used